

**Technical Data Sheet** 

## XIAMETER<sup>™</sup> OFS-6194 Silane

Features & Benefits	• • •	Reactive alkoxy functionality reacts with water to form siloxane polymers Bonds to hydroxyl bearing surfaces (e.g., metal oxides, silicaceous, cellulosics) Provides hydrophobicity Forms flexible silicone polymers
Composition	•	Dimethyldimethoxy silane
Applications	•	Surface treatment to increase hydrophobicity

• Reactive intermediate for siloxane synthesis

**Typical Properties** Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result	
Appearance		Clear, water white liquid	
Purity	%	> 95%	
Specific Gravity		0.86	
Boiling Point	°C	81.4	
Molecular Weight	g/mol	120.2	
Flash Point (closed cup)	°C	10	

Description	XIAMETER <sup>™</sup> OFS-6194 Silane is dimethyldimethoxy silane (CAS# 1112-39-6).
Handling Precautions	PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER SERVICE.
Storage	Product should be stored between 0°C and 50°C (32° and 122°F) in original, unopened containers.

Limitations	This product is neither tested nor represented as suitable for medical or pharmaceutical uses.
	Not intended for human injection. Not intended for food use.
Health And Environmental Information	To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.
	For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

http://www.xiameter.com

## LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

